

## CLAIMS

1. An analytical instrument having improved arrangement of reagent portion, the analytical instrument comprising a flow  
5 path for moving a sample containing blood cells, an introduction port for introducing the sample into the flow path, a reagent portion arranged in the flow path, and an electron detection medium for obtaining information necessary for analyzing an analysis target component  
10 contained in the sample in relation with an amount of electrons transferred;

wherein the reagent portion contains an electron mediator for supplying an electron taken from the analysis target component in the sample to the electron detection  
15 medium, and wherein at least part of the reagent portion is positioned adjacent to the introduction port.

2. The analytical instrument according to claim 1, wherein the reagent portion is arranged upstream from the electron  
20 detection medium in a direction of flow of the sample while being separated from the electron detection medium.

3. The analytical instrument according to claim 2, wherein the reagent portion is in a solid state and dissolves when  
25 the sample is supplied to the flow path.

4. The analytical instrument according to claim 3, wherein

center-to-center distance between the reagent portion and the electron detection medium is so set that, when the sample contains the analysis target component in maximum amount of a predetermined detection range, electron transfer  
5 from the maximum amount of analysis target component to the electron mediator is substantially completed before the electron mediator becomes able to supply electrons to the electron detection medium.

10 5. The analytical instrument according to claim 3, wherein the content of the electron mediator in the reagent portion is so set that, when the sample contains the analysis target component in maximum amount of a predetermined detection range, the electron mediator can receive all the electrons  
15 taken from the maximum amount of analysis target component.

6. The analytical instrument according to claim 1, wherein the electron detection medium contains a color former.

20 7. The analytical instrument according to claim 6, wherein the electron detection medium is provided by causing a porous body which is sparingly soluble in the sample to support the color former.

25 8. The analytical instrument according to claim 1, wherein the electron detection medium comprises a conductor.

9. The analytical instrument according to claim 8, wherein the conductor is utilized for applying voltage to the electron mediator when the sample is supplied to the flow path.

5

10. The analytical instrument according to claim 1, wherein the reagent portion contains an oxidoreductase for taking an electron from the analysis target component contained in the sample and supplying the electron to the electron mediator.

10

11. The analytical instrument according to claim 1, further comprising an additional reagent portion which is provided separately from said reagent portion and which contains an oxidoreductase for taking an electron from the analysis target component contained in the sample and supplying the electron to the electron mediator.

15

12. The analytical instrument according to claim 11, wherein the additional reagent portion is arranged between said reagent portion and the electron detection medium in a direction of flow of the sample in the flow path.

20

13. The analytical instrument according to claim 12, wherein said reagent portion is larger in area in plan view than the additional reagent portion.

25

14. The analytical instrument according to claim 12, wherein

said reagent portion is larger than the additional reagent portion in length in the direction of flow of the sample.

15. The analytical instrument according to claim 12, wherein  
5 said reagent portion is smaller in thickness than the additional reagent portion.

16. The analytical instrument according to claim 15, wherein  
the thickness of said reagent portion is 15 to 80 % of the  
10 thickness of the additional reagent portion.

17. The analytical instrument according to claim 12, wherein  
said reagent portion has an area in plan view which is 1.5  
to 10 times an area in plan view of the electron detection  
15 medium in the flow path.

18. The analytical instrument according to claim 12, wherein  
said reagent portion has a length which accounts for 50 to  
90 % of distance from the sample introduction port to an end  
20 of the additional reagent portion on the sample introduction  
port side.

19. The analytical instrument according to claim 12, wherein  
said reagent portion and the additional reagent portion are  
25 designed to dissolve when the sample is introduced into the  
flow path.

20. The analytical instrument according to claim 10, wherein the oxidoreductase is glucose dehydrogenase (GDH).

21. The analytical instrument according to claim 20, wherein  
5 the oxidoreductase is PQQGDH,  $\alpha$ GDH or CyGDH.

22. The analytical instrument according to claim 1, wherein the electron mediator is a Ru complex.

10 23. The analytical instrument according to claim 1, wherein the analysis target component in the sample is glucose.

24. The analytical instrument according to claim 1, wherein the flow path is designed to generate a capillary force.

15

25. An analytical instrument comprising: a flow path for moving a sample containing blood cells; an introduction port for introducing the sample into the flow path; an electron detection medium for obtaining information necessary for  
20 analyzing an analysis target component contained in the sample in relation with an amount of electrons transferred, the electron detection medium comprising a porous body which is sparingly soluble in the sample and in which a color former is supported; an electron mediator layer which  
25 contains an electron mediator for supplying an electron taken from the analysis target component contained in the sample to the electron detection medium and which dissolves

when the sample is supplied to the flow path; and an oxidoreductase layer which contains an oxidoreductase for taking an electron from the analysis target component contained in the sample and supplying the electron to the electron mediator and which dissolves when the sample is  
5 supplied to the flow path;

wherein the electron mediator layer, the oxidoreductase layer and the electron detection medium are aligned in the flow path in mentioned order from an upstream side in a  
10 direction of flow of the sample.

26. The analytical instrument according to claim 25, wherein the electron mediator layer is larger in area in plan view than the oxidoreductase layer.  
15

27. The analytical instrument according to claim 25, wherein the electron mediator layer is larger than the oxidoreductase layer in length in the direction of flow of the sample.  
20

28. The analytical instrument according to claim 25, wherein the electron mediator layer is smaller in thickness than the oxidoreductase layer.

25 29. The analytical instrument according to claim 28, wherein the thickness of the electron mediator layer is 15 to 80 % of the thickness of the oxidoreductase layer.

30. The analytical instrument according to claim 25, wherein the electron mediator layer has an area in plan view which is 1.5 to 10 times an area in plan view of the electron detection medium in the flow path.

5

31. The analytical instrument according to claim 25, wherein the electron mediator layer has a length which accounts for 50 to 90 % of distance from the sample introduction port to an end of the oxidoreductase layer on the sample  
10 introduction port side.

32. The analytical instrument according to claim 25, wherein the electron mediator is a Ru complex.

15 33. An analytical method comprising the steps of: supplying, in a state in which a sample containing blood cells is moving, electrons taken from an analysis target component contained in the sample to an electron mediator so that electron transfer from the analysis target component to the  
20 electron mediator is substantially completed in said state;

causing electron transfer between the electron mediator and an electron detection medium in a state in which the movement of the sample is stopped; and

performing computation necessary for analyzing the  
25 analysis target component based on information obtained through the electron detection medium.

34. The analytical method according to claim 33, wherein the electron detection medium contains a color former.

35. The analytical method according to claim 33, wherein the  
5 analysis target component is glucose.